

Em104-s415

STPC Elite 133Mhz 486 CPU board with LCD, CRT & LAN



Features

- * Support STPC Elite CPU up to 133Mhz
- * Onboard 32MB SDRAM
- * Support 1 x 10/100 Mbps Ethernet
- * Support LCD/CRT display
- * Support PC/104 expansion bus

System

CPU	STPC Elite CPU 133Mhz
Cache	8KB
Memory	Onboard 32MB SDRAM up to 128MB
Chipset	STPC Elite + Winbond W83977
BIOS	Phoenix-AWARD PnP Flash BIOS
ATA/IDE	1 x PIO3, support 2 IDE drives
Flash Disk	1 x Disk On Chip Socket
Watchdog Timer	127-level Reset

I/O

Serial Port	1 x RS-232 port (COM1) 1 x RS-232/422/485 port (COM2)
Parallel Port	SPP/EPP/ECP mode
Floppy Disk	Support 2 Floppy disk drives
KB / MS	1 x PS2 K/B and Mouse
Digital I/O	16-bit Digital Input / Output
Expansion Bus	1 x 16bit ISA-based PC/104 interface

Ethernet

Chipset	Realtek 8100BL 10/100base-T
---------	-----------------------------

Display

Graphics Chipset	TOPRP TP6508 or CHIPS C&T65550 up to 1MByte Video RAM
Graphics Interface	CRT support up to 1024 x 768 TFT/DSTN/STN/Mono/EL up to 1024 x 768 LCD support 24-bit TTL

Mechanical & Environmental

Operating Temperature	0 ~ 60°C (32 ~ 140°F)
Operating Humidity	0% ~ 90% (non-condensing)
Dimension (L x W)	96 x 90mm
Weight	0.10 kg (0.22lb)

Ordering Information

Em104-s415DVL	Onboard 32MB SDRAM with display and LAN	
Cable Kit	CBK-06-0415-00	Page 5-3